## Beattyville Water Works Water Quality Report 2020

Water System ID: KY0650024 WTP Manager: Tony Snowden 606-464-1000 CCR Contact: Tony Snowden 606-464-1000 tsnowden@beattyville.org Mailing Address: P.O. Box 307 Beattyville, KY 41311 Meeting location and time: 28 Railroad Street, Suite A Second Mondays at 6:00 PM

Beattyville treats surface water from the North Fork of the Kentucky River. An analysis of the susceptibility of the water supply to contamination indicates that susceptibility is generally moderate. Areas of concern include highways, bridges, railroads, municipal sewer lines, and hazardous waste users. Customers in the Farm Ridge, Cressmont, and Spencer Ridge areas are supplied by Jackson County Water Association. Jackson County treats surface water from Beulah (Tyner) Lake that has a high susceptibility. Considerable concern for both water sources include soil and stream bank erosion, and fertilizer and pesticide runoff. The complete Source Water Assessment Plans can be reviewed at the respective water system offices during normal business hours.

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects may be obtained by calling the Environmental Protection Agency's Safe Drinking Water Hotline (800-426-4791).

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the ground, it dissolves naturally occurring minerals and, in some cases, radioactive material, and may pick up substances resulting from the presence of animals or from human activity. Contaminants that may be present in source water include: Microbial contaminants, such as viruses and bacteria, (sewage plants, septic systems, livestock operations, or wildlife). Inorganic contaminants, such as salts and metals, (naturally occurring or from stormwater runoff, wastewater discharges, oil and gas production, mining, or farming). Pesticides and herbicides, (stormwater runoff, agriculture or residential uses). Organic chemical contaminants, including synthetic and volatile organic chemicals, (by-products of industrial processes and petroleum production, or from gas stations, stormwater runoff, or septic systems). Radioactive contaminants, (naturally occurring or from oil and gas production or mining activities). In order to ensure that tap water is safe to drink, EPA prescribes regulations that limit the amount of certain contaminants in water provided by public water systems. FDA regulations establish limits for contaminants in bottled water to provide the same protection for public health.

Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. EPA/CDC guidelines on appropriate means to lessen the risk of infection by Cryptosporidium and other microbial contaminants are available from the Safe Drinking Water Hotline (800-426-4791).

## **Information About Lead:**

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. Your local public water system is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at http://www.epa.gov/safewater/lead.

## Some or all of these definitions may be found in this report:

Maximum Contaminant Level (MCL) - the highest level of a contaminant that is allowed in drinking water. MCLs are set as close to the MCLGs as feasible using the best available treatment technology.

Maximum Contaminant Level Goal (MCLG) - the level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs allow for a margin of safety.

Maximum Residual Disinfectant Level (MRDL) - the highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.

Maximum Residual Disinfectant Level Goal (MRDLG) - the level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Below Detection Levels (BDL) - laboratory analysis indicates that the contaminant is not present.

Not Applicable (N/A) - does not apply.

Parts per million (ppm) - or milligrams per liter, (mg/l). One part per million corresponds to one minute in two years or a single penny in \$10,000.

Parts per billion (ppb) - or micrograms per liter, (µg/L). One part per billion corresponds to one minute in 2,000 years, or a single penny in \$10,000,000.

Parts per trillion (ppt) - one part per trillion corresponds to one minute in 2,000,000 years, or a single penny in \$10,000,000,000.

Parts per quadrillion (ppq) - one part per quadrillion corresponds to one minute in 2,000,000,000 years or one penny in \$10,000,000,000.

Picocuries per liter (pCi/L) - a measure of the radioactivity in water.

Millirems per year (mrem/yr) - measure of radiation absorbed by the body.

Million Fibers per Liter (MFL) - a measure of the presence of asbestos fibers that are longer than 10 micrometers.

Nephelometric Turbidity Unit (NTU) - a measure of the clarity of water. Turbidity has no health effects. However, turbidity can provide a medium for microbial growth. Turbidity is monitored because it is a good indicator of the effectiveness of the filtration system.

Variances & Exemptions (V&E) - State or EPA permission not to meet an MCL or a treatment technique under certain conditions.

Action Level (AL) - the concentration of a contaminant which, if exceeded, triggers treatment or other requirements that a water system shall follow.

Treatment Technique (TT) - a required process intended to reduce the level of a contaminant in drinking water.

Spanish (Español) Este informe contiene información muy importante sobre la calidad de su agua beber. Tradúzcalo o hable con alguien que lo entienda bien.

To request a paper copy call (606) 464-5007.

le health	effects descri	bed for many	regulated	l con	taminants,	a person w	ould have	to drink 2 liters of water	
s reduced m	onitoring require	ements for certain	n contamina	ants to	o less often tl	han once per	year because	the concentrations of these	
1 1	8	fice during busin	ess hours.						
nt Test R	esults	Beattyville	Water	Wor	ks			1	
		Report	Range		Date of Viola	Violation	Likely Source of		
MCL	MCLG	Level	of Detection		Sample		Contamination		
2	2	0.039	0.039	to	0.039	Oct-20	No	Drilling wastes; metal refineries; erosion of natural deposits	
tion Byp	roducts and	Precursors	•				•	•	
		1.34							
TT*	N/A	(lowest	1.00	to	1.97	2020	No	Naturally present in environment.	
		average)	(mor	nthly	ratios)				
emoval achi	eved to the % T(	DC removal requi	red. Annua	laver	age must be	1.00 or greater	for complia	nce.	
MRDL	MRDLG	1.31			-	-			
= 4	= 4	(highest	0.4	to	2.2	2020	No	Water additive used to control microbes.	
		average)						merobes.	
		42							
60	N/A	(high site	16	to	68	2020	No	Byproduct of drinking water disinfection	
		average)	(range of	indiv	idual sites)			disincetion	
		55							
80	N/A	(high site	16	to	91	2020	No	Byproduct of drinking water disinfection.	
		average)	(range of	indiv	idual sites)			disincetion.	
Contami	nants							•	
AL=		0.0795							
1.3	1.3	(90 <sup>th</sup>	0.0023	to	0.171	Aug-20	No	Corrosion of household plumbing systems	
		percentile)						systems	
AL=		0							
15	0	(90 <sup>th</sup>	0	to	6	Aug-20	No	Corrosion of household plumbing systems	
		percentile)				-		systems	
A	lowable	Highest Single			Lowest	Violation	Violation		
1	evels Measuremen		t	Monthly %		Like		y Source of Turbidity	
No more th	an 1 NTU*							·	
Less than 0.3 NTU in 95% of monthly samples		0.243			100	No	Soil runoff		
	rel for a li rt are from t s reduced m to vary sign request by c mt Test R MCL 2 tion Byp TT* emoval achie MRDL = 4 60 80 Contamin AL = 1.3 AL = 1.5 No more th Less than (	relife time to have retained from the most recent to s reduced monitoring require to vary significantly from ye request by contacting our off mt Test Results   MCL MCLG   2 2   tion Byproducts and TT* N/A   moval achieved to the % TO MRDL MRDLG   =4 =4   60 N/A   80 N/A   Contaminants 1.3   AL= 1.3   15 0   Allowable Levels   No more than 1 NTU*   Less than 0.3 NTU in	rel for a lifetime to have a one-in-a-metric are from the most recent testing done in action is reduced monitoring requirements for certain to vary significantly from year to year. Some request by contacting our office during busines in the result of the second seco	rel for a life time to have a one-in-a-million chart are from the most recent testing done in accordance vision of the data request by contacting our office during business hours.   mutrate from the most recent testing done in accordance vision of the data request by contacting our office during business hours.   mutrate from the most recent testing done in accordance vision of the data request by contacting our office during business hours.   mutrate from the most recent testing done in accordance vision of the data request by contacting our office during business hours.   mutrate from the most recent testing done in accordance vision of the data request by contacting our office during business hours.   mutrate from the most recent testing done in accordance vision of the data request by contacting our office during business hours.   MCL MCL Report Report   2 2 0.039 0.039   2 2 0.039 0.039   tion Byproducts and Precursors 1.34 1.00   TT* N/A (lowest 1.00   moval achieved to the % TOC removal required. Annual waverage) 0.42   MRDL MRDLG 1.31   = 4 = 4 (high site 16   average) (range of 55 80   N/A (high site 16 av	rel for a lifetime to have a one-in-a-million chance of the request monitoring requirements for certain contaminants to to vary significantly from year to year. Some of the data in thirequest by contacting our office during business hours.   Int Test Results Beattyville Water Wor   MCL MCLG Level of Detect   2 2 0.039 0.039 to   2 2 0.039 0.039 to   tion Byproducts and Precursors   TT* N/A (lowest 1.00 to   MRDL MRDLG 1.31 (monthly monthly   envolatable 0 N/A (highest 0.4 to   MRDL MRDLG 1.31 1.6 to average) (range of indiv   80 N/A (high site 16 to average) (range of indiv   80 N/A (high site 16 to average) (range of indiv   1.3 1.3 90 <sup>th</sup> 0.0023 to percentile)   AL= 0 (90 <sup>th</sup> ) 0 to percentile)   AL= <	rel for a lifetime to have a one-in-a-million chance of having the second and the most recent testing done in accordance with administrative is reduced monitoring requirements for certain contaminants to less often the to vary significantly from year to year. Some of the data in this table, though request by contacting our office during business hours.INTENTING INTENTING THE ResultsBeattyville Water WorksMCLMCLGLevelMCLMCLGLevel220.039to220.039to220.039to220.039to1.341.00toTT*N/A(lowest)average)(monthly ratios)emoval achieved to the % TOC removal required. Annual average must beMRDLMRDLG1.31=4=4(highest)4260N/A60N/A(high site)16to68average)(range of individual sites)80N/A(high site)131.3(90th)0.0023to0.171percentile)1.3AL =01.31.31.3(90th)0to601401501501501610171001810019100	rel for a lifetime to have a one-in-a-million chance of having the describe   rel for a lifetime to have a one-in-a-million chance of having the describe   a dimensional to have a one-in-a-million chance of having the describe   a dimensional to have a one-in-a-million chance of having the describe   a dimensional to have a one-in-a-million chance of having the describe   a dimensional to have a one-in-a-million chance of having the describe   s reduced monitoring requirements for certain contaminants to less often than once pery to vary significantly fom year to year. Some of the data in this table, though representative equest by contacting our office during business hours.   Mate of Report Range Date of Sample   MCL MCLG Level of Detection Sample   2 2 0.039 0.039 to 0.039 Oct-20   tion Byproducts and Precursors   TT* N/A 1.34 1.00 to 1.97 2020   average) average (monthly ratios) 2020 2020 2020   tion Byproducts and Precursors I.31 0.4 to 2.2 2020   emoval achieved to the % TOC removal arequired. Annual average must be 1.00 or greatered (high site 1	Test ResultsBeattyville Water WorksMCLMCLGReportRange of DetectionDate of SampleViolation220.0390.039to0.039Oct-20No220.0390.039to0.039Oct-20Notion Byproducts and Precursors1.34 (lowest average)1.00to1.97 (monthly ratios)2020Nomrval achieved to the % TOC removal required. Annual average must be1.00 or greater for complian (monthly ratios)NoNoMRDL = 4I.31 = 40.4to2.22020No60N/A (high site average)0.4to2.22020No60N/A (high site average)16to68 (average)2020No80N/A (high site average)16to91 (average)2020NoContaminantsAL = 150(90 <sup>th</sup> (90 <sup>th</sup> )0to6Aug-20NoAllowable Highest Single LevelsLowest MeasurementViolation Monthly%Likely SNo more than 1 NTU* Less than 0.3 NTU in0.243100NoNo	

<b>Regulated Contamina</b>	nt Test R	esults	Jackson (	Co. Water	· Associatio	n		
Contaminant			Report	F	Range	Date of	Violation	Likely Source of Contamination
[code] (units)	MCL	MCLG	Level	of Detection		Sample		
Combined radium	5	0	0.577	0.577 t	to 0.577	Mar-19	No	Erosion of natural deposits
(pCi/L)								
Barium								
[1010] (ppm)	2	2	0.008	0.008 t	o 0.008	Apr-20	No	Drilling wastes; metal refineries; erosion of natural deposits
Fluoride								
[1025] (ppm)	4	4	0.08	0.08 t	io 0.08	Apr-20	No	Water additive which promotes strong teeth
Nitrate								Fertilizer runoff; leaching from
[1040] (ppm)	10	10	0.209	0 t	o 0.209	Mar-20	No	septic tanks, sewage; erosion of natural deposits
Disinfectants/Disinfec	tion Byp	roducts and	Precurso	ors		•	•	
Total Organic Carbon (ppm)			1.82					
(measured as ppm, but	TT*	N/A	(lowest	1.27 t	io 3.41	2020	No	Naturally present in environment
reported as a ratio)			average)	(mont	hly ratios)			
*Monthly ratio is the % TOC r	emoval achi	eved to the % T(	DC removal re	equired. Ann	ual average mus	t be 1.00 or gre	ater for com	pliance.
Other Constituents								
Turbidity (NTU) TT	Allowable Hig		Highest S	lighest Single		Violation		
* Representative samples	1	Levels Meas		nent	Monthly %		Likely Source of Turbidity	
Turbidity is a measure of the	No more than 1 NTU*		0.1			No		
clarity of the water and not a contaminant.	Less than 0.3 NTU in 95% of monthly samples				100		Soil runoff	
contaniillant.								